

- > Energy Saving 51 Watt Integrated LED
- > Daylight 5000K CCT
- > Long Life - Lasts 45 years* or 50,000 Hours**
- > Maintenance Free — No Bulb Replacements
- > Reliable - Starts in cold environments to -4°F (-20°C)
- > Durable - IP65 rated with corrosion resistant stainless steel clips
- > Linkable - Connect up to 7 5400 lm vapor tight fixtures from one power source
- > 5 Year Limited Warranty

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

4' Vapor Tight

5400 lm | 120-277VAC | Model 54465161 | Part VT-4-54-850-MV-D



SPECIFICATIONS

Model	54465161
Part	VT-4-54-850-MV-D
Certification #	54465161-1
Description	4' Vapor Tight
Input Voltage (VAC)	120-277
Wattage	51
Dimmability	Dimmable, 0-10v
Average Rated Life ¹	50,000 hours
Typical Lumens ²	5400
CCT ³	5000K
Location Rating	UL Wet (IP65 Rated)
CRI ⁴	≥80
Beam Angle	120°
Operating Temperature	Min -4°F (-20° C) Max 113°F (45° C)
Power Factor	>0.9
R9	27
DUV	-0.00168
Operating Frequency (Hz)	50/60
DLC Product ID	P4H7GGKX

¹ Hours lifetime with 70% lumen maintenance

² Thermally stable typical lumens (±10%)

³ Thermally stable CCT (±10%)

⁴ Color rendering index/Ra

* Based on 3 hours average daily use

** 70% lumens maintenance over 50,000 hours





4' Vapor Tight

5400 lm | 120-277VAC | Model 54465161 | Part VT-4-54-850-MV-D

SHIPPING INFORMATION

Model	54465161
Part	VT-4-54-850-MV-D
UPC	849489002293
Product Dimensions (L x W x H in.)	48 x 4 19/32" x 3
Product Dimensions (L x W x H cm.)	122 x 11.7 x 7.6
Product Weight (lbs.)	4.91
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	2
Master Carton Bar Code	50849489002298
Master Carton Dimensions (L x W x H in.)	4' 2 29/32" x 7 5/16" x 5 11/32"
Master Carton Dimensions (L x W x H cm.)	129.3 x 18.6 x 13.6
Master Carton Weight (lbs)	12.82
Pallet Quantity	160

COMPATIBILITY

Motion Sensors: 90600145

Dimmers:	
Brand	Model#
Lutron	DVTV-IV
Lutron	DVSTV-WH
Lutron	MSCL-OP153M-WH
Lutron	DVSTV-453PH-WH
Lutron	NFTV-WH
Lutron	DVTV-WH
Lutron	IP710-DLZ

AVAILABLE ACCESSORIES

Model	Part	Description	Wattage	Input Voltage	Case Pack
90600145	NA	Step Dimming Motion Sensor	NA	120-277	4

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.ETiSSL.com/fcc15b

TO ORDER:
www.ETiSSL.com
 Call: 1.855.ETi.SSLI
 1.855.384.7754

ETi Solid State Lighting, Inc.
 720 Corporate Woods Parkway
 Vernon Hills, IL 60061
 Phone: 855.384.7754
 Fax: 847.383.6256