



Product Data Sheet

General Masking Tape



Product Description:

Economy Grade Masking Tape for general use and simple jobs in the building, construction and industrial sectors. Recommended to remove within 30 hours.

- Good addition even on uneven surfaces - Well conformable to most shaped surfaces
- Hand Tearable - Easy removal, if removed as soon as paint is dry, without leaving residue

Item ID Numbers Here:

MSTE4318W, MSTE4324W,
MSTE4336W, MSTE4348W

Wrap-Tite, Inc.
6200 Cochran Rd.
Solon, Ohio 44139
Toll Free: 888-WRAP-TITE
Fax: 440-349-5432
www.wraptite.com -
info@wraptite.com

Backing:

Saturated Semi-Crepe Paper

Adhesive:

Natural Rubber and cross-linked Resins

Color:

White

Elongation (% At Break)

8 % (PSTC 131)

Tensile Strength

18 lb./ in (PSTC 131)

Adhesion to Steel

14 oz./in width (PSTC 101)

Total Thickness:

4.3 Mil

Temperature Range:

140° F

Packaging

N/A

Country of Origin

N/A

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.